



**Catalogue**  
**FOOD SERVICE**  
**Chapter**  
**DISTRIBUTION**

**Model**

19036263

28/05/2020

**HOT TROLLEY CCF-10 220V 1N 50/60Hz**

The special design of the chamber and rack rails enables the free circulation of hot air through all the trolley, leading to the creation of a uniform airflow distribution, ensuring that food is always maintained at its right temperature.

Two (2) forced-air electric resistors in each cabinet body to ensure that heat is distributed through all the unit in a perfectly even, uniform manner. Safety security mechanism in resistors in case of malfunctioning.

Doubled wall with an injected CFC-free, ecological polyurethane 40 Kg/m<sup>3</sup> density isolation.

With its highly-insulated walls, heat losses are reduced thus obtaining energy savings.

Thermostat to control and regulate the temperature at desired setpoint: from 0° to 90° C.

Stamped control panel. Protected from receiving direct impacts since it is located in a safe place.

Durable, robust bumper along whole trolley base to protect body from direct impacts.

Waveless evaporation tray system to control humidity in the chamber and prevent food from drying out.

Sound-proof castors of 160 mm diameter, two of them with brakes for an easy handling and safer use.

Rack rail system that can be quickly removed for easy cleaning.

Up to eight (8) plates of a maximum diameter of 300 mm can be stored per level.

Food can be hold inside the trolley directly on plates by using of rod shelves or in Gastronorm pans.

10 GN2/1 rack rails with 60 mm separation between rack rails.

Heating system by using two (2) forced-air electric resistors in each cabinet body to ensure that heat is distributed through all the unit. The special design of the chamber and rack rails enables the creation of a uniform, even airflow distribution, ensuring that food is always maintained at its right temperature.

Horizontal handle system for fast opening and closing of door.

Automatic locking mechanism in hinges: when door is in a position of less than a 90° angle it gets fully closed, thus avoiding loss of temperature and achieving energy savings.

Four (4) sound-proof castors of 160 mm diameter, two of them with brakes for an easy handling and safer use. Non-marking, special rubber bumpers to protect against direct impacts along the whole trolley base.


Key locked door.

Entirely made of stainless steel.

Rod shelves and Gastronorm pans are not included. To be ordered separately.

**DIMENSIONS**

X Width	799 mm	X Gross width	980 mm
Y Depth	789 mm	Y Gross depth	830 mm
Z Height	1190 mm	Z Gross height	1360 mm
Net Weight	101,0 kg	Gross Weight	105,0 kg
Net volume	0,750 m <sup>3</sup>	Gross volume	1,106 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	1,921 kW
Amperage (A)	8,5A
Heating power	1,90 kW
Voltage	220V - 1N
Electric frequency	50/60Hz

**OTHERS**

Number of doors	1
-----------------	---



Catalogue  
**FOOD SERVICE**

Chapter  
**DISTRIBUTION**

Model

19036263

28/05/2020

